

## SAFETY DATA SHEET

### SECTION 1 – IDENTIFICATION

Product name: **B-Lock Vine Paint**  
Synonyms: None  
Product use: Vine seal  
Product restrictions:  
Manufacturer name: Nutrient Technologies, Inc.  
Address: 1092 E. Kamm Ave., Dinuba, CA 93618  
General phone number: (559) 595-8090  
Transportation emergency #: CHEMTREC: 800-424-9300

### SECTION 2 – HAZARD(S) IDENTIFICATION



Signal word: Warning  
GHS Class: Eye Irritant, Category 2, Skin Irritant, Category 2

Hazard statements: Causes eye and skin irritation

#### Precautionary Statements

Prevention: Wear protective clothing, gloves, eye, and face protection.  
Response: Wash hands thoroughly after handling.  
Disposal: Dispose of unused contents, container and other wastes in accordance with local, state, and federal regulations.

### SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

<b>Component</b>	Propylene Glycol, Limestone, Titanium Dioxide, Boric Acid
<b>CAS Number</b>	57-55-6, 1317-65-3, 13463-6-7, 10043-35-3
<b>Weight%</b>	1-5%, 10-30%, 10-30%, 5%

### SECTION 4 – FIRST AID MEASURES

Eye contact: Immediately flush opened eyes with plenty of water for 15-20 minutes. Get medical attention if irritation persists.

Skin contact: Immediately wash skin with soap and water. Get medical attention if irritation persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. Seek immediate medical attention.

Ingestion: If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

## SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog when fighting fires involving this product.

Specific hazards arising from the chemical: May emit oxides of carbon under fire conditions.

Protective equipment: As in any fire, wear self-contained breathing apparatus (SCBA), MSHA/NIOSH approved, and full protective gear.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions: Evacuate area and keep unnecessary and unprotected personnel from entering spill area. Do not walk through spilled material. Put on appropriate personal protective equipment (section 8).

Environmental precautions: Avoid runoff into waterways, drains and sewers.

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent spreading by diking or other means.

Methods for cleanup: Clean up spills immediately and place in suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water.

## SECTION 7 – HANDLING and STORAGE

Precautions for handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Precautions for storage: Store in a cool, dry, well-ventilated area away from heat, combustible and incompatible materials. Keep container tightly closed when not in use.

## SECTION 8 – EXPOSURE CONTROLS, PERSONAL PROTECTION

Occupational exposure limits: Titanium Dioxide TLV-TWA: 10mg/m<sup>3</sup>  
Boric Acid TLV-TWA: 10mg/m<sup>3</sup>

Appropriate engineering controls: Use appropriate engineering control such as enclosures, exhaust ventilation, or other means to control airborne levels below the recommended exposure limits. Good general ventilation should be sufficient to control airborne levels.

Personal protective equipment: Wear splash-proof goggles, chemical resistant gloves. Protective equipment for the face and body should be selected based on the task being performed; avoid product contact with skin and clothing.

## SECTION 9 – PHYSICAL and CHEMICAL PROPERTIES

Odor/appearance:	Viscous pink liquid, indeterminate odor
Odor threshold:	Not determined
Boiling point:	100 °C (212 °F)
Melting point:	Not applicable
Flash point:	None.
Flammability:	Not applicable
Density:	1.224 g/cm <sup>3</sup> (10.2 lbs/gal)
Solubility:	Not determined
Vapor density:	Not Applicable
Vapor pressure:	Not Applicable
Evaporation rate:	Not Applicable
pH:	7-9
Viscosity:	3000-5000cps
Partition coefficient: (n-octanol/water)	Not Applicable
VOC content:	Material VOC: 32gm/L (includes water)

## SECTION 10 – STABILITY and REACTIVITY

Chemical stability:	Stable under normal temperatures and pressures
Hazardous Polymerization:	Not reported.
Conditions to avoid:	Heat, flames, incompatible materials, and freezing temperatures (below 0 °C/32 °F).
Incompatible materials:	Oxidizing agents. Strong acids and alkalis.

## SECTION 11 – TOXICOLOGICAL INFORMATION

Acute Toxicity (Oral LD50):	No LD50 available. May be harmful if swallowed.
Acute Toxicity (Dermal LD50):	No LD50 available. May irritate the skin.
Acute Toxicity Inhalation LC50:	No LC50 available. May be harmful if inhaled.

### Likely routes of exposure:

Skin irritation	May irritate the skin.
Eye irritation:	May irritate the eyes.
Skin sensitization:	Not tested.
Carcinogenic:	Not listed by IARC, NTP, or OSHA.
Chronic effects:	None known.
Other hazards:	None known.

## SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity:	No ecotoxicity data was found for this product.
Environmental fate:	No environmental information found for this product.

## SECTION 13 – DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in accordance with local, state and federal regulations. Arrange disposal in accordance to the EPA and/or state and local guidelines. Empty containers may retain product residues.

## SECTION 14 – TRANSPORT INFORMATION

UN transport shipping name: Not restricted as dangerous good.  
Transport hazard class: None  
UN Identification number: None  
Packing group: None  
IATA Shipping name: Not restricted as dangerous good.

## SECTION 15 – REGULATORY INFORMATION

Proprietary ingredients:  
Propylene Glycol TSCA Inventory status – listed  
Limestone TSCA Inventory status – listed  
Titanium Dioxide TSCA Inventory status – listed  
Boric Acid TSCA Inventory status – listed

SARA 313 This material does not contain any chemical components with known CAS numbers that exceed the threshold reporting levels established by SARA Title III, Section 313.

## SECTION 16 – ADDITIONAL INFORMATION

HMIS rating:  
Health Hazard 1  
Fire Hazard 1  
Reactivity 0  
Other x

SDS revision date: 30-May-15